



NEW MODEL 2022!

Hydraulic steering choice

The NEW Lindec® LC900H rider has a powerful 26 Hp Honda petrol engine which drives twin 4-blade or optional 5-blade rotors to a top rotor speed of 170 rpm's. Choose between soft or quick hydraulic steering.

The new Lindec® LC900H rider has new and better features such as; "flip up" guard-rings, "flip up" seat frame, fuel and water tank guard.

The machine is CE-certified according to safety demands and machine directives 2006/42/EG and AFS 2008:3.





Heavy duty tank protection

A well-placed protection to protect both fuel and water tank.



Flip-up guardrings

For quicker and simplifying blade change and to minimize space during transport.



Protection for fuel tap
A smart & easy protection for fuel tap.



Powerful lifting points
New powerful lifting points
for safer and better lifting.



Flip up seat frame

Service, maintenance and repair

Folding seat frame for easy access to the engine and drive shafts.

LC900H **Basic data** GX690 **Engine** Dimensions (L x W x H) 201x103x136cm **Panning Path Width** 2x94cm Rotors (Diameter) 91 cm Rpm 170 rpm 385 kg Weight **Fuel Capacity** 23 lit **Water Capacity** 23 lit

Accessories	
Dolly wheel set	art. no: LCDW
Additional LED lights	art. no: LC900250
Trowel pan	art. no: 11619 / 11619-5
Trowel blades	art. no: 11512 / 11512-5
Combination blades	art. no: 11562
Engine catalyst GX690	art. no: 11085

Standard features

- · Hydraulic steering
- · Powerful hydraulic cylinders and hoses
- 26 Hp Honda engine (GX690)
- · Tank and fuel tap cover
- Tilt-up protective rings for faster blade changes and enable less space during transport.
- Torque converter/Torque Converter clutch
- Specially designed spider-arms that have seals to prevent concrete and concrete water from entering into the spider cross for reduced required maintenance.
- U-joints with extra seals for best durability and easier steering.
- Flip-up seat frame for easy access to engine, clutch and drive shafts.
- Four adjustable LED lights with the option to supplement with extras.
- High speed rotor (170 rpm) for superior results
- Electrical main power switch
- · Two adjustable hand trowel holders
- · Waterproof electrical connectors
- · Counter of engine speed and hours
- Spray system
- · Central lifting points including lifting straps
- Document box (service manual)
- Cup holder
- Adjustable chair
- · Engine oil monitor
- 12 V outlet
- CE approved

ab lindec® endeavours to provide correct information about technical properties and handling of its products. However, while ab lindec® has no control over the way in which the products are mixed and laid, or the conditions under which they set, ab lindec® can in no way be held responsible. ab lindec® is only responsible for the quality of the products at the time of delivery.

